

County Surveyor's Record, Douglas County, Oregon

15090

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

blaze.

A hemlock, 10 ins. diam., bears N. 69° W., 23 lks.
dist., no marks visible on healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 28 S
R 9 W R 8 W
S 13 | S 18
S 24 | S 19
1972

Reset iron pipe alongside iron post.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, yew, maple and
madrone; undergrowth, vine maple, hazel, salal and fern.

From the cor. of secs. 17, 18, 19 and 20.

N. 3° 35' W., bet. secs. 17 and 18.

Descend 375 ft. over N. slope, through heavy timber and
moderate undergrowth.

- 8.60 East Fork of Coquille River, 10 lks. wide, course
N. 45° W.; asc. 90 ft. over broken S. slope.
- 11.40 Coos Bay Wagon Road, paved, 40 lks. wide, bears
N. 60° W., and S. 60° E.
- 25.30 Top of ascent, slopes W.; desc. 25 ft. over NW. slope.
- 31.20 Creek, 2 lks. wide, course S. 80° W.; asc. 5 ft. over
broken S. slope.
- 35.12 Creek, 8 lks. wide, course S. 30° W.; asc. 115 ft. over
SE. slope.
- 40.77 The 1/4 sec. cor. of secs. 17 and 18, perpetuated and
recorded by James W. Byron, Deputy County Surveyor, in
1957, monumented with an iron pipe, 2 ins. diam., firmly
set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE
T 28 S
1/4 S 18 | S 17
R8W
1957

from which original bearing trees

A fir, 75 ins. diam., bears S. 60° E., 6 lks.
dist., no marks visible on opened blaze.

A fir, 84 ins. diam., bears S. 35° W., 11 lks.
dist., with scribe marks BT visible on opened
blaze.

and trees marked by Byron