

County Surveyor's Record, Douglas County, Oregon

15091

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 15 ins. diam., bears N. 27° E., 65 lks. dist., with healed double blaze.

A hemlock, 13 ins. diam., bears N. 36° W., 38 lks. dist., with healed double blaze.

N. 2° 49' E., beginning new measurement.

Ascend 70 ft. over SE. slope.

6.55 Spur, slopes S. 80° E.; desc. 15 ft. over NE slope.

8.35 Creek, 2 lks. wide, course S. 60° E.; asc. 255 ft. over SE. slope.

9.05 Spur, slopes S. 35° E.; desc. 55 ft. over SE. slope, leaving heavy timber.

23.50 Ravine, drains E.; asc. 20 ft. over SE. slope.

24.25 Spur, slopes S. 45° E.; desc. 5 ft. over NE. slope.

26.50 Creek, 12 lks. wide, course S. 40° E.; asc. 225 ft. over SE. slope, also power line bears S. 45° E., and N. 45° W.

39.00 Enter heavy timber.

39.57 The cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 28 S R 8 W			
S 7 S 8			
S 18 S 17			
1972			

from which

A fir, 15 ins. diam., bears N. 37° E., 54 lks. dist., mkd. T28S R8W S8 BT.

A fir, 8 ins. diam., bears S. 62° E., 42 lks. dist., mkd. T28S R8W S17 BT.

A fir, 18 ins. diam., bears S. 17° W., 39 lks. dist., mkd. T28S R8W S18 BT.

A fir, 18 ins. diam., bears N. 40° W., 15 lks. dist., mkd. T28S R8W S7 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, alder, yew, maple and madrone; undergrowth, vine maple, hazel, salal, poison oak and fern.

From the cor. of secs. 8, 9, 16 and 17, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron pipe, 2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.