

# County Surveyor's Record, Douglas County, Oregon

15092

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYOR'S OFFICE

T 28 S  
S 8 | S 9  
S 17 | S 16  
R 8 W  
1957

*Handwritten notes:*  
112 80 10  
2000

from which the original bearing trees

A hemlock, 13 ins. diam., bears N. 16 1/2° E., 10 lks. dist., with healed blaze. Re-marked by Byron with scribe mks. 28S R8W BT visible on partially healed double blaze.

A fir, 64 ins. diam., bears S. 62° E., 16 lks. dist., with fragmentary scribe mks. visible on weathered bark blaze. Re-marked by Byron, with scribe marks T28S R8W S16 CS BT visible on bark blaze.

A hemlock, 20 ins. diam., bears S. 69° W., 25 lks. dist., with no scribe mks. visible on opened blaze. Re-marked by Byron, with scribe marks T28S R8W S17 C visible on partially healed blaze. (Record, S. 69° E.)

A hemlock, 32 ins. diam., bears N. 45 1/2° W., 31 lks. dist., with scribe mks. BT visible on opened blaze. Re-marked by Byron, with healed double blaze.

S. 89° 19' W., bet. secs. 8 and 17.

Descend 130 ft. over SW. slope through heavy timber and light undergrowth.

- 3.00 Creek, 6 lks. wide, course S. 70° E.; asc. 475 ft. over SE. slope.
- 14.90 Spur, slopes N. 50° E.; desc. 60 ft. over NW. slope.
- 20.70 Creek, 4 lks. wide, course N. 45° E.; asc. 515 ft. over NE. slope.
- 40.37 Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 8 W  
1/4 S 8  
S 17  
1972

from which

A fir, 17 ins. diam., bears N. 13° E., 73 lks. dist., mkd. 1/4 S8 BT.

A fir, 10 ins. diam., bears S. 14° W., 15 lks. dist., mkd. 1/4 S17 BT.

Ascend 120 ft. over broken SE. slope.

- 45.00 Burnt Ridge Road, dirt, 20 lks. wide, bears S. 15° W., and N. 15° E.