

County Surveyor's Record, Douglas County, Oregon

15093

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

66.20 Spur, slopes S.; desc. 20 ft. over SW. slope.

68.90 Ravine, drains S. 45° E.; asc. 175 ft. over SE. slope.

80.74 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, maple, madrone and
yew; undergrowth, hazel, salal, huckleberry and fern.

S. 89° 15' W., bet. secs. 7 and 18.

Ascend 110 ft. over SE. slope, across old clear cut area
through scattering timber and moderate undergrowth.

8.40 Spur, slopes S. 10° W., desc. 490 ft. over SW. slope.

15.00 Power line, bears S. 85° E., and N. 85° W.

40.12 Point for the 1/4 sec. cor. of secs. 7 and 18, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a
drill hole, in solid rock, with top marked

T 28 S R 8 W
S 7
1/4 S 18
1972

from which

A fir, 12 ins. diam., bears N. 16 1/4° E., 140 1/2 lks.
dist., mkd. 1/4 S7 BT.

A fir, 10 ins. diam., bears S. 82 1/4° W., 147 lks.
dist., mkd. 1/4 S18 BT.

Descend 575 ft. over SW. slope.

79.84 The cor. of secs. 7, 12, 13 and 18 on the West boundary
of the Tp., perpetuated and recorded by Floyd Frear,
Deputy County Surveyor, in 1953, from original evidence
no longer in existence, further perpetuated and recorded
by James W. Byron, Deputy County Surveyor, in 1956,
monumented with an iron pipe, 2 ins. diam., firmly set,
the top, 4 ins. below the surface of the ground, with
brass cap mkd.

COUNTY SURVEYOR'S OFFICE
Coos Co. R 9 W S 12 | S 7 R 8 W Douglas Co.
S 13 | S 18
1956

from which the remains of bearing trees marked by Frear

A fir stump, 72 ins. diam., bears S. 83° E., 36 lks.
dist., with scribe mks. T28S R8W S18 BT visible
on bark blaze.

A fir stump, 72 ins. diam., bears S. 32° W., 70 lks.
dist., with scribe mks. T28S R9W S13 BT visible
on bark blaze.