

# County Surveyor's Record, Douglas County, Oregon

15095

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 60 ins. diam., bears S. 52° E.,  
106 lks. dist., with scribe marks 1/4 S8 CS BT  
visible on open blaze.

A sawed hemlock stump, 10 ins. diam., bears  
N. 79° W., 109 lks. dist., with scribe marks BT  
visible on bark blaze.

and new bearing trees

A fir, 60 ins. diam., bears S. 67° E., 121 lks.  
dist., mkd. 1/4 S8 BT.

A hemlock, 4 ins. diam., bears S. 72° W., 89 lks.  
dist., mkd. X BT.

Corner falls on East edge of dirt road, 10 lks. wide,  
bears N. and S.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, yew, maple and madrone; undergrowth,  
salal, huckleberry, fern and rhododendron.

Subdivision of Section 10, T. 28 S., R. 8 W.,  
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 10 and 15.

N. 0° 41' E., on the N. and S. center line of sec. 10.

Ascend 20 ft. over SW. slope, through scattering timber  
and light undergrowth, marking and blazing the true line.

- 1.90 Spur, slopes N. 70° W.; desc. 40 ft. over NW. slope.
- 2.95 Edge of open field, bears NE. and W.; also ravine,  
drains SW.; asc. 180 ft. over SE. slope, across open  
land.
- 16.75 Edge of open field, bears NW. and SE.; enter scattering  
timber and light undergrowth.
- 24.80 Enter moderate timber, edge bears N. and S.; spur,  
slopes S. 35° E.; desc. 40 ft. over NE. slope.
- 31.50 Creek, 3 lks. wide, course SE.; asc. 125 ft. over S.  
slope.
- 34.45 Spur, slopes S. 80° E.; desc. 30 ft. over NE. slope.
- 35.50 Dry creek, 8 lks. wide, drains E.; asc. 70 ft. over  
S. slope.
- 40.06 Point for the center 1/4 sec. cor. of sec. 10, at inter-  
section with the E. and W. center line of sec. 10.

*FD OK PER M 109-53  
11-82 BY BRIDAKER*

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

*FD OK  
3/91 M 111-70*

C 1/4 S 10  
1969

from which