

County Surveyor's Record, Douglas County, Oregon

15096

Subdivision of Section 10, T. 28 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS

A cedar, 32 ins. diam., bears S. 27 1/2° E., 60 lks.
dist., mkd. C 1/4 S10 BT.

A fir, 10 ins. diam., bears S. 43 1/4° W., 43 1/2 lks.
dist., mkd. C 1/4 S10 BT.

Ascend 525 ft. over steep SE. slope.

60.00 Point for the center N 1/16 sec. cor. of sec. 10.

Set an iron post, 10 ins. long, 1 in. diam., 4 ins. in
drill hole in solid rock, with brass cap mkd.

C
N 1/16 | S 10
C
1969

from which

A fir, 38 ins. diam., bears S. 1 1/2° E., 71 lks.
dist., mkd. CN 1/16 S10 BT.

A madrone, 25 ins. diam., bears N. 67° W., 60 lks.
dist., mks. CN 1/16 S10 BT.

Ascend 560 ft. over steep SE. slope.

62.50 Enter heavy timber and moderate undergrowth, edge bears
S. and W.

76.20 Top of rock bluff, 140 ft. high, bears NE. and SW.

79.94 The 1/4 sec. cor. of secs. 3 and 10.

From the 1/4 sec. cor. of secs. 10 and 11.

S. 89° 23' W., on the E. and W. center line of sec. 10.

Descend 150 ft. over broken SW. slope, through pasture
land.

30.10 Edge of open pasture, bears N. and S., enter moderate
timber and undergrowth.

32.10 Ravine, drains S. 20° E.; asc. 60 ft. over E. slope.

39.25 The center 1/4 sec. cor. of sec. 10.

Ascend 20 ft. over E. slope.

42.95 Ravine, drains S. 30° E.; continue asc. 200 ft. along
S. slope.

54.15 Ravine, drains S. 30° E.; continue asc. 410 ft. over
SE. slope.

64.20 Spur, slopes S.; desc. 190 ft. over SW. slope.

65.40 Enter logged area, edge bears N. and S.

78.67 The 1/4 sec. cor. of secs. 9 and 10.

From the center N 1/16 sec. cor. of sec. 10.