

County Surveyor's Record, Douglas County, Oregon

15009

T. 25 S., R. 2 W., Willamette Meridian, Oregon.

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, township 26 south, range 2 west; a portion of the east boundary, township 25 south, range 3 west; and a portion of the subdivisional lines and subdivision of sections 31 and 32, township 25 south, range 2 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The corner of townships 25 and 26 south, ranges 2 and 3 west, was established by Addison R. Flint, in 1855, when he surveyed the north and east boundaries of township 26 south, range 3 west.

The north boundary of township 26 south, range 2 west, was surveyed by John A. McQuinn, in 1883.

The east boundary of township 25 south, range 3 west was surveyed by Laban H. Wheeler, in 1883.

The north boundary of township 26 south range 2 west and the east boundary of township 25 south, range 3 west, were retraced and the subdivisional lines of township 25 south, range 2 west, were surveyed by Hezekiah H. Johnson, in 1900.

The north boundary of township 26 south, range 2 west, was retraced and in part, resurveyed by Charles N. Collier, in 1913-14.

The Collier retracement and resurvey of the north boundary was checked and corner recoveries found to be correct by Fred Mensch, in 1918. Mensch also investigated field conditions in township 25 south, range 2 west, and in doing so retraced the south three miles of the east boundary of township 25 south, range 3 west, and the meridional lines in the south tier of sections and the line between sections 30 and 31, township 25 south, range 2 west.

The east boundary of township 25 south, range 3 west, was resurveyed by Norman D. Price, in 1943-44.

A portion of the north boundary of township 26 south, range 2 west, was resurveyed by Irving Zirpel, Jr. and William W. Glenn, in 1959.

Certain original corners within township 25 south, range 2 west, were remonumented without survey, by Floyd A. Brooks, in 1962.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were re-established and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947 and 1973, and the special Instructions dated June 29, 1972, under Group Number 786, Oregon, July 12, 1974, under Group Number 848, Oregon, and November 1, 1974, under Group Number 854, Oregon.