

# County Surveyor's Record, Douglas County, Oregon

15100

T. 25 S., R. 2 W., Willamette Meridian, Oregon.

CHAINS

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

The geographic position of the closing corner of sections 34 and 35, on the south boundary of the township, as scaled from the Mace Mountain, Oregon, quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 20.6' N.                      Longitude 123° 54.7' W.

The mean magnetic declination is 19° 45' E.

Dependent Resurvey of a Portion of the North Boundary,  
T. 26 S., R. 2 W., Willamette Meridian, Oregon.

(Restoring the 1883 survey by John A. McQuinn, Deputy Surveyor, the 1900 retracement by Hezekiah H. Johnson, Deputy Surveyor, the 1913-14 resurvey by Charles N. Collier, U. S. Surveyor, and the 1959 resurvey by Irving Zirpel, Jr. and William W. Glenn, Cadastral Surveyors)

Beginning at the cor. of sec. 2 and 3 only, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, alongside of which is the original basalt stone, 16 x 10 x 7 ins., with 4 notches on W. and 2 notches on E. face, with brass cap mkd.

T 25 S R 2 W  
S 35  
S 3 | S 2  
T 26 S R 2 W  
1959

from which an original bearing tree and bearing object

A fir, 48 ins. diam., bears S. 82 1/2° W., 248 1/2 lks. dist., with healed blaze.

A rock in place, 4 x 3 1/2 x 3 ft. high, bears S. 20° E., 54 lks. dist., with marks T26S R2W on NW. face.

and a bearing tree mkd. by G. Robert Lecklider, RLS No. 362, in 1959.

A fir, 44 ins. diam., bears S. 44 1/2° E., 56 lks. dist., with healed blaze.

N. 89° 06' W., on the N. bdy. of sec. 3, marking and blazing the true line.

Descend 70 ft. over SW. slope, through scattering timber and moderate undergrowth.

3.10 Creek, 2 lks. wide, course S.; asc. 1 ft. along S. slope.

3.12 The closing cor. of secs. 34 and 35, T. 25 S., R. 2 W., established by G. Robert Lecklider, RLS No. 362, in 1960, monumented with an iron pipe, 36 ins. long, 1/2 in.