

County Surveyor's Record, Douglas County, Oregon

15101

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

diam., firmly set, protruding 12 ins. above ground, from which a bearing tree and bearing object mkd. by Lecklider:

A fir, 15 ins. diam., bears N. 49 1/4° W., 13 lks. dist., with healed blaze.

A rock in place, 54 x 40 x 30 ins. bears N. 12° E., 10 lks. dist., with marks C|C BO visible on S. face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 S R 2 W
C|C
S 34 | S 35
S 3
T 26 S R 2 W
1974

from which a new bearing tree

An alder, 18 ins. diam., bears N. 35° E., 76 lks. dist., mkd. T25S R2W S35 CC BT.

Ascend 5 ft. along S. slope.

- 4.50 Top of ascent, slopes S.; desc. 120 ft. along S. slope.
- 18.15 Dirt road, 15 lks. wide, bears N. 35° W.
- 20.77 Creek, 1 lk. wide, course S. 20° W.; asc. 25 ft. over SE. slope.
- 23.875 Point for the E 1/16 sec. cor. of sec. 34 only, T. 25 S., R. 2 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in ground, with brass cap mkd.

E 1/16 S 34
1974

from which

A fir, 12 ins. diam., bears N. 52 1/2° E., 57 lks. dist., mkd. E 1/16 S34 BT.

A fir, 6 ins. diam., bears N. 42° W., 68 1/2 lks. dist., mkd. E 1/16 S34 BT.

Ascend 30 ft. over SE. slope.

- 26.00 Top of ascent, slopes S.; desc. 15 ft. over SW. slope.
- 29.70 Bottom of descent, slopes S.; asc. 30 ft. over SE. slope.
- 35.70 Top of ascent, slopes S.; desc. 15 ft. over SW. slope.
- 39.11 The 1/4 sec. cor. of sec. 3 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 2 ins.