

County Surveyor's Record, Douglas County, Oregon

15102

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

above ground, alongside of which is the original basalt stone, 16 x 10 x 4 ins., firmly set, mkd. 1/4 on S. face, with brass cap mkd.

$\frac{1}{4} S 3$
 T 26 S R 2 W
 1959

from which a locally established bearing tree described by Zirpel and Glenn, in 1959.

A fir, 33 ins. diam., bears S. 55° W., 120 lks. dist., with healed blaze.

and a bearing tree mkd. by Zirpel and Glenn

A fir, 41 ins. diam., bears S. 29° E., 220 lks. dist., with healed blaze.

West, beginning new measurement.

Descend 30 ft. over SW. slope, through scattering timber and moderate undergrowth.

5.52 Point for the 1/4 sec. cor. of sec. 34 only, T. 25 S., R. 2 W., At proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 S R 2 W
 $\frac{1}{4} S 34$
 T 26 S R 2 W
 1974

from which

A fir, 7 ins. diam., bears N. 61° E., 77 lks. dist., mkd. 1/4 S34 BT.

A fir, 10 ins. diam., bears N. 16 1/4° W., 86 1/2 lks. dist., mkd. 1/4 S34 Bt.

Descend 215 ft. over SW. slope.

16.00 Creek, 2 lks. wide, course S. 5° E.; asc. 325 ft. over SE. slope.

38.99 The cor. of secs. 3 and 4 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, alongside of which is an unmarked basalt stone, 16 x 14 x 8 ins. loosely set, with brass cap mkd.

T 25 S R 2 W
 $\frac{S 34}{S 4 \frac{1}{2} S 3}$
 T 26 S R 2 W
 1959

from which the original bearing trees

A fir, 46 ins. diam., bears S. 16 3/4° E., 512 lks. dist., with healed blaze.