

County Surveyor's Record, Douglas County, Oregon

15104

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

- A fir, 34 ins. diam., bears N. 65° E., 28 lks. dist., with illegible scribe marks visible on bark.
- A sawed fir stump, 25 ins. diam., bears S. 10° E., 22 lks. dist., no marks visible.
- A fir, 40 ins. diam., bears N. 55° W., 5 lks. dist., with scribe marks 2 R2 6 visible on bark blaze.

and a bearing tree mkd. by Collier, in 1913

- A partially uprooted yew, 12 ins. diam., bears S. 60° W., 51 lks. dist., mkd. T26S R2W S5 BT on partially healed blaze.

and new bearing trees

- A cedar, 8 ins. diam., bears S. 13° E., 89 lks. dist., mkd. T26S R2W S 4 BT.
- A cedar, 7 ins. diam., bears S. 24° W., 59 lks. dist., mkd. T26S R2W S5 BT.

S. 89° 15' W., on the N. bdy. of sec. 5.

Descend 60 ft. over NW. slope, through heavy timber and dense undergrowth.

2.10 Creek, 2 lks. wide, course N.; asc. 150 ft. over NE. slope.

6.17 The closing cor. of secs. 32 and 33, T. 25 S., R. 2 W., re-established at proportionate measurement by V. W. Hosford, RLS No. 253, in 1960, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, from which bearing trees mkd. by Hosford:

- A root hole, bears N. 47° E., 18 lks. dist., with a down hemlock alongside, 13 ins. diam., with scribe marks T25S CC S33 253 BT visible on open blaze.

- A hemlock, 16 ins. diam., bears N. 12° W., 69 lks. dist., with scribe marks R2W CC S32 253 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

	C	C	
T 25 S		R 2 W	
S 32		S 33	
	—		
	S 5		
T 26 S		R 2 W	
			1972

from which new bearing trees

- A fir, 8 ins. diam., bears N. 37° E., 45 lks. dist., mkd. T25S R2W S33 CC BT.