

County Surveyor's Record, Douglas County, Oregon

15105

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	Deposit the iron pipe alongside the iron post.
	Ascend 70 ft. over NE. slope.
14.30	Spur, slopes N.; desc. 50 ft. over NW. slope.
18.30	Bottom of descent, slopes N.; asc. 110 ft. over NE. slope.
24.00	Spur, slopes N.; desc. 40 ft. over NW. slope.
25.90	Ravine, drains. N.; asc. 315 ft. over NE. slope.
27.06	The E 1/16 sec. cor. of sec. 32 only, T. 25 S., R. 2 W., established by V. W. Hosford, RLS No. 253, in 1960, monumented with an X scratched atop a sandstone outcrop, from which bearing trees mkd. by Hosford: <div style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 25° E., 53 lks. dist., with healed blaze.</div> <div style="margin-left: 40px;">A madrone, 10 ins. diam., bears N. 4° W., 12 lks. dist., with scribe marks E 1/16 S32 253 BT visible on bark blaze.</div> <p>At the corner point</p> <p>Set a brass tablet, 3 ins. diam., 3 1/2 ins. stem, in a drill hole, in solid rock, mkd.</p> <div style="text-align: center; margin-left: 100px;"> <u>E 1/16 S 32</u> 1972 </div> <p>from which a new bearing tree</p> <div style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 46° W., 45 lks. dist., mkd. E 1/16 S32 BT.</div> <p>Ascend 15 ft. over NE. slope.</p>
28.10	Ridge, bears NW. and SE.; desc., 290 ft. over SW. slope.
41.12	The 1/4 sec. cor. of sec. 5 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 2 ft. base, to top, with brass cap mkd. <div style="text-align: center; margin-left: 100px;"> <u>T 26 S R 2 (S) W</u> 1/4 S 5 1959 </div> <p>from which bearing trees mkd. by Zirpel and Glenn</p> <div style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 50° E., 26 lks. dist., with healed blaze.</div> <div style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 68 1/2° W., 29 lks. dist., with healed blaze.</div>
	S. 89° 25' W., beginning new measurement.