

County Surveyor's Record, Douglas County, Oregon

15107

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

remains of the original corner tree, a decayed fir stump, size indeterminate, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1972, with an iron post, 2 ins. diam., firmly set in the remains of the corner tree, protruding 8 ins. above ground, with brass cap mkd.

T 25 S R 2 W
S 32
S 6 | S 5
T 26 S
1972

from which the remains of bearing trees mkd. by Zirpel and Glenn, in 1959

A root hole, bears S. 68° E., 75 lks. dist., with a down fir alongside, 25 ins. diam., with healed blaze.

A root hole, bears S. 30° W., 36 lks. dist., with a down fir alongside, 16 ins. diam., with healed blaze.

and bearing trees mkd. by the County Surveyor

A fir, 15 ins. diam., bears S. 75° W., 53 lks. dist., with scribe marks T26S R2W S6 CS BT visible on open blaze.

A fir, 17 ins. diam., bears N. 15° W., 13 lks. dist., with scribe marks T25S R2W S32 CS BT visible on open blaze.

No suitable tree available in section 5.

Land, mountainous.
Soil, rocky clay and rock outcroppings.
Timber, fir, cedar hemlock, pine, yew, maple, chinquapin, dogwood, and madrone; undergrowth, vine maple, ocean spray, hazel, rhododendron, manzanita, salal, huckleberry, and Oregon grape,

S. 89° 31' W., on the N. bdy. of sec. 6.

Ascend 150 ft. over NE. slope. through heavy timber and dense undergrowth.

6.60 Spur, slopes N.; desc. 5 ft. over SW. slope.

7.54 The closing cor. of secs. 31 and 32, T. 25 S., R. 2 W., re-established by V. W. Hosford, RLS No. 253, in 1960, and perpetuated by John M. Powell, Deputy County Surveyor, in 1972, monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

T 25 S R 2 W
C C
S 31 | S 32
S 6
1972

from which bearing trees mkd. by Hosford