Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 2 w., Willamette Meridian, Oregon

CHAINS	
	A cedar, 22 ins. diam., bears N. 67° E., 30 lks. dist., with healed blaze.
	A cedar, 28 ins. diam., bears N. 68° W., 43 lks. dist., with healed blaze.
	Descend 155 ft. over SW. slope.
31.75	Ravine, drains S.; asc. 40 ft. over SE. slope.
38.60	Spur, slopes S.; desc. 10 ft. over SW. slope.
39.72	The 1/4 sec. cor. of sec. 6 only, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd. 1/4 — T 25 S / S 6 W — R 2 T 25 S 1967 from which bearing trees mkd. by Collier, in 1913 A fir, 60 ins. diam., bears S. 31° E., 39 lks. dist., with healed blaze. A fir, 56 ins. diam., bears S. 54° W., 36 lks. dist., no marks visible on opened blaze. and the remains of bearing trees mkd. by Tracy A fir, 14 ins. diam., bears S. 54° E., 23 lks. dist., with healed blaze. A root hole, bears S. 32° W., 22 lks. dist., with a down fir alongside, 12 ins. diam., with scribe marks 1/4 S6 CS BT visible on open blaze. and a new bearing tree A fir, 8 ins. diam., bears S. 39° W., 78 lks. dist., mkd. 1/4 S6 BT.
	S. 88° 58' W., beginning new measurement. Descend 15 ft. over SW. slope.
7.66	Point for the 1/4 sec. cor. of sec. 31 only, T. 25 S., R. 2 W., hereinafter described. Descend 730 ft. over SW. slope.
38.22	The cor. of Tps. 25 and 26 S., RS. 2 and 3 W., monumented with an iron post, 3 ins. diam., firmly set protruding 8 ins. above ground, with brass cap mkd. T 25 S R 3 W | R 2 W S 36 | S 31 S 1 | S 6 T 26 S 1943