

County Surveyor's Record, Douglas County, Oregon

15110

Dependent Resurvey, Portion of East Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 18 ins. diam., bears N. 53 1/2° E., 103 lks.
dist., mkd. 1/4 S31 BT.

A hemlock, 10 ins. diam., bears S. 60° E., 91 lks.
dist., mkd. 1/4 S31 BT.

Ascend 2 ft. over S. slope.

44.20 Spur, slopes S. 60° E.; desc. 5 ft. over NE. slope.

44.45 The 1/4 sec. cor. of sec. 36 only, re-established by Norman D. Price, in 1943, monumented with an iron post, 1 in. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

1/4 S 36 |
1943

from which the remains of bearing trees mkd. by Price

A fir stump, 9 ins. diam., bears S. 8 1/2° W., 7 lks.
dist., with scribe marks 1/4 S36 BT visible on
open blaze.

A root hole, bears N. 38° W., 9 lks. dist., with
down fir, alongside, 14 ins. diam., no marks
visible.

and bearing trees mkd. by the County Surveyor

A fir, 7 ins. diam., bears S. 76° W., 60 lks.
dist., with healed blaze.

A hemlock, 10 ins. diam., bears N. 22° W., 34 lks.
dist., with healed double blaze.

N. 1° 55' E., beginning new measurement.

Descend 40 ft. over NE. slope, through heavy timber and light undergrowth.

10.75 From this point, the 1/4 sec. cor. of sec. 31 only, T. 25 S., R. 2 W., erroneously established by Price, in 1943, based on the 1900 retracement by Johnson, bears East, 0.060 chs. dist., monumented with an iron post, 1 in. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

| 1/4 S 31
1943

from which the remains of bearing trees mkd. by Price

A fir stump, 36 ins. diam., bears N. 6 1/2° E., 94
lks. dist., with scribe marks 1/4 S31 BT visible
on open blaze.

A fir, 12 ins. diam., bears S. 52° E., 9 lks.
dist., with healed blaze.

and a bearing tree mkd. by the County Surveyor

A fir, 7 ins. diam., bears N. 67° E., 63 lks.
dist., with healed blaze.