

County Surveyor's Record, Douglas County, Oregon

15141

Dependent Resurvey, Portion of East Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Add marks AM 1972 to brass cap.

Ascend 15 ft. over nearly level ground.

13.75 Dirt road, 10 lks. wide, bears S. 70° E. and N. 70° W.

16.65 Spur, slopes W.; desc. 10 ft. over N. slope.

19.60 Kelly Creek, 60 lks. wide, course S. 30° E.; asc. 105 ft. over S. slope.

38.90 The original closing cor. of secs. 30 and 31. T. 25 S., R. 2 W., monumented with an iron pipe, 2 ins. diam., firmly set, protruding 8 ins. above ground, with a basalt stone alongside, 16 x 10 x 4 ins., firmly set, with 5 grooves on N., 1 groove on S., and CC on E. faces, with brass cap mkd.

T 25 S	T 25 S	
R 3 W	S 30	CC
S 36	S 31	
	R 2 W	
	1943	

from which the remaining original bearing tree

A fir, 38 ins. diam., bears S. 73° E., 55 lks. dist., no marks visible on open and decayed blaze.

and a bearing tree mkd. by Price

A fir, 28 ins. diam., bears S. 61° E., 103 lks. dist., with healed blaze.

Ascend 5 ft. over nearly level ground,

43.40 Rock Creek Road, 30 lks. wide, bears E. and W.

44.46 The cor. of secs. 25 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

T 25 S	T 25 S	
S 25	S 25	T 25 S
S 36	R 2 W	
R 3 W	S 30	
	1943	

from which the remains of the original bearing trees

A decayed fir snag, 14 ins. diam., bears N. 69° E., 27 lks. dist., no marks visible.

A decayed hemlock stump, 16 ins. diam., bears S. 67 1/2° E., 41 lks. dist., no marks visible.

A root hole, bears S. 51 1/2° W., 58 lks. dist., with a down hemlock alongside, 16 ins. diam., no marks visible.

A root hole, bears N. 61 1/4° W., 31 lks. dist., with a down hemlock alongside, 30 ins. diam., no marks visible.

and the remains of bearing trees mkd. by Price