

County Surveyor's Record, Douglas County, Oregon

15112

Dependent Resurvey, Portion of East Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A red cedar snag, 34 ins. diam., bears S. 43° W.,
86 lks. dist., with scribe marks T25S R3W S36 BT
visible on open blaze.

A white fir snag, 14 ins. diam., bears N. 39° W.,
48 lks. dist., with healed blaze.

and a bearing tree mkd. by the County Surveyor

A yew, 6 ins. diam., bears N. 41° W., 38 lks.
dist., with scribe marks T25S R3W S25 BT visible
on open double blaze.

and a new bearing tree

A hemlock, 15 ins. diam., bears S. 55° W., 87 lks.
dist., mkd. T25S R3W S36 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, yew, maple, chin-
quapin, and dogwood; undergrowth, vine maple, hazel,
rhododendron, manzanita, salal, fern, and Oregon grape.

(Restoring the 1900 survey by Hezekiah H. Johnson,
Deputy Surveyor, and
the 1918 retracement by Fred Mensch,
Deputy Surveyor)

From the cor. of secs. 25, 26, 35, and 36, remonumented
by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins.
diam., firmly set, protruding 4 ins. above ground,
alongside of which is the original basalt stone, 18 x 10
x 8 ins., firmly set, mkd. with 1 notch on S. and 1
notch on E. face, with brass cap mkd.

T 25 S R 2 W	
S 26	S 25
S 35	S 36
1962	

from which the original bearing trees

A fir, 45 ins. diam., bears N. 23° E., 59 lks.
dist., with healed blaze.

A fir, 32 ins. diam., bears S. 70° E., 78 lks.
dist., with healed blaze.

A fir, 30 ins. diam., bears S. 31° W., 129 1/2 lks.
dist., with healed blaze.

A fir, 75 ins. diam., bears N. 40° W., 43 lks.
dist., with healed blaze.

N 2° 44' W., bet. secs. 25 and 26, marking and blazing
the true line.

Ascend 145 ft. over SE. slope. through heavy timber and
dense undergrowth.