

County Surveyor's Record, Douglas County, Oregon

15113

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

9.05 Ridge, bears NE. and SW.; desc. 195 ft. over NW. slope.

22.34 Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 26 | S 25
1974

*RENEWED 2/3/92
OCSO
C.S. 6/23*

from which

A hemlock, 16 ins. diam., bears N. 47° E., 84 lks. dist., mkd. S 1/16 S25 BT.

A hemlock, 18 ins. diam., bears S. 73 1/2° W., 37 lks. dist., mkd. S 1/16 S26 BT.

Descend 80 ft. over NW. slope.

30.45 Rock cliff, edge bears E. and W.; desc. 505 ft. over steep N. slope.

38.20 Gravelled road, 15 lks. wide, bears N. 80° E. and W.

44.68 The 1/4 sec. cor. of secs. 25 and 26, remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap mkd.

1/4
S 26 | S 25
T 25 S | R 2 W
1962

from which the original bearing trees

A fir, 40 ins. diam., bears S. 59° E., 29 lks. dist., with healed blaze.

A hemlock, 29 ins. diam., bears S. 35° W., 39 lks. dist., with scribe marks S2 visible on opened blaze.

and a bearing tree mkd. by Brooks

A cedar, 19 ins. diam., bears N. 33 1/2° W., 10 1/2 lks. dist., with scribe marks 1/4 S26 BT visible on open blaze

N. 1° 00' E., beginning new measurement.

Descend 30 ft. over N. slope. through heavy timber and light undergrowth.

3.25 Creek, 1 lk. wide, course N. 50° W.; desc. 35 ft. over NW. slope.

10.80 Creek, 1 lk. wide, course N. 35° W., asc. 55 ft. over SW. slope.

20.55 Spur, slopes W.; desc. 180 ft. over NW. slope.

25.90 Dirt road, 15 lks. wide, bears E. and W.