

# County Surveyor's Record, Douglas County, Oregon

15115

Dependent Resurvey, Portion of Subdivisional Lines  
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 59° W., 32 lks. dist., with a down hemlock alongside, 14 ins. diam., with fragmentary scribe marks visible on open blaze. (Record, N. 65° W.)

and the remains of bearing trees mkd. by Lecklider

A hemlock snag, 14 ins. diam., bears N. 89° E., 51 lks. dist., with fragmentary scribe marks visible on open blaze.

A root hole, bears S. 46° E., 45 lks. dist., with a down hemlock alongside, 12 ins. diam., no marks visible.

A root hole, bears S. 72° W., 44 lks. dist., with a down hemlock alongside, 12 ins. diam., no marks visible.

A hemlock, 11 ins. diam., bears N. 50° W., 47 lks. dist., with scribe marks RE4079 BT visible on open double blaze.

and new bearing trees

A hemlock, 10 ins. diam., bears N. 43 1/2° E., 66 1/2 lks. dist., mkd. T25S R2W S26 BT.

A hemlock, 16 ins. diam., bears S. 60 1/2° E., 72 lks. dist., mkd. T25S R2W S35 BT.

S. 1° 09' E., bet. secs. 34 and 35.

Ascend 490 ft. over NW. slope, through scattering timber and dense undergrowth.

35.35 Top of ascent, slopes W.; desc. 115 ft. over SW. slope.

40.54 The 1/4 sec. cor. of secs. 34 and 35, re-established and recorded by G. Robert Lecklider, RLS No. 362, in 1960 monumented with a steel tube, 3/4 in. diam., firmly set, protruding 6 ins. above ground, from which bearing trees mkd. by Lecklider:

A fir, 20 ins. diam., bears N. 35° W., 54 lks. dist., with healed double blaze.

A fir, 33 ins. diam., bears S. 32 1/2° E., 90 lks. dist., with healed double blaze.

A fir, 24 ins. diam., bears S. 23° W., 21 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 2 W  
1/4  
S 34 | S 35  
1974

from which new bearing trees

A fir, 10 ins. diam., bears N. 73° E., 72 lks. dist., mkd. 1/4 S35 BT.

A fir, 28 ins. diam., bears S. 40 1/2° W., 38 lks. dist., mkd. 1/4 S34 BT.

Deposit steel tube alongside iron post.

S 1° 11' E., beginning new measurement.

Descend 525 ft. over SW. slope. changing to W.

20.305 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.