

County Surveyor's Record, Douglas County, Oregon

15116

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

S 1/16
S 34 | S 35
1974

from which

A chinquapin, 7 ins. diam., bears N. 43° E., 27
lks. dist., mkd. S 1/16 S35 BT.

A fir, 15 ins. diam., bears S. 17 1/2° W., 46 lks.
dist., mkd. S 1/16 S34 BT.

Descend 455 ft. along W. slope.

36.71 Ravine, drains. S. 40° W.; desc. 30 ft. over SW. slope.

38.58 The closing cor. of secs. 34 and 35, T. 25 S., R. 2 W.,
From this point, the cor. of secs. 2 and 3 only, T. 26 S.,
R. 2 W., bears S. 89° 06' E., 3.12 chs. dist., herein
before described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, yew, chinquapin, and
madrone; undergrowth, vine maple, hazel, arrowwood,
salal, Oregon grape, rhododendron, poison oak, and fern.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 16' W., bet. secs. 26 and 35.

Ascend 130 ft. over SE. slope. through heavy timber and
dense undergrowth.

7.80 Ridge, bears NE. and SW.; desc. 90 ft. over NW. slope.

20.00 Point for the E 1/16 sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

E 1/16 $\frac{S\ 26}{S\ 35}$
1974

from which

A fir, 20 ins. diam., bears N. 33° W., 17 lks.
dist., mkd. E 1/16 S26 BT.

A fir, 15 ins. diam., bears S. 13° W., 86 1/2 lks.
dist., mkd. E 1/16 S35 BT.

Descend 145 ft. over NW. slope.

40.00 The 1/4 sec. cor. of secs. 26 and 35, perpetuated and re-
corded by Vernon R. Tracy, Deputy County Surveyor, in
1967, occupied by the original corner tree, a hemlock
snag, 6 ins. diam., with scribe marks 4S visible on
opened S. face, alongside, of which is an iron post, 2
ins. diam., firmly set, protruding 10 ins. above ground,
with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 25 S R 2 W
1/4 $\frac{S\ 26}{S\ 35}$
1967

from which the original bearing trees

A hemlock, 11 ins. diam., bears N. 10° W., 3 lks.
dist., with scribe marks 4S visible on opened
blaze.

A hemlock, 27 ins. diam., bears S. 8° E., 25 lks.
dist., with scribe marks 4S visible on opened
blaze. (Record, S. 4° W.)