

County Surveyor's Record, Douglas County, Oregon

15117

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	<p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A hemlock, 21 ins. diam., bears N. 64° W., 7 lks. dist., with scribe marks 1/4 S26 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">A hemlock, 21 ins. diam., bears S. 25° W., 63 1/2 lks. dist., with scribe marks 1/4 S35 CS BT visible on open double blaze.</p> <p>and a reference monument</p> <p style="padding-left: 40px;">An iron post, 28¹/₂ ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 11 1/2° W., 15 lks. dist., with brass cap mkd. T25S R2W S35 RM 1974, and an arrow pointing to the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 33' W., beginning new measurement.</p> <p>Descend 65 ft. over NW. slope, through heavy timber and light undergrowth.</p> <p>9.05 Bottom of descent, slopes N.; asc. 25 ft. along N. slope.</p> <p>18.05 Top of ascent, slopes N.; desc. 20 ft. over NW. slope.</p> <p>18.50 Gravelled road, 15 lks. wide, bears N. 65° E. and S. 35° W., in curve.</p> <p>20.04 The W 1/16 sec. cor. of secs. 26 and 35, established by Nick Juliano, Registered Logging Engineer, No. 3449, in 1973, monumented with an iron post, 2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border: none;"> <tr><td>T 25 S R 2 W</td></tr> <tr><td>W 1/16 $\frac{S 26}{S 35}$</td></tr> <tr><td>1973</td></tr> </table> </div> <p>from which bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 21 1/2° E., 5 1/2 lks. dist., with a railroad spike driven into base.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 1° W., 16 lks. dist., with a railroad spike driven into base.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 33 1/2° E., 33 1/2 lks. dist., mkd. W 1/16 S26 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 23 1/2° W., 28 lks. dist., mkd. W 1/16 S35 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 33' W., beginning new measurement.</p> <p>Descend 250 ft. over NW. slope, through heavy timber and dense undergrowth.</p> <p>11.91 Ravine, drains. N. 30° E.; asc. 10 ft. over NE. slope.</p> <p>13.56 Spur, slopes N. 10° E.; desc. 135 ft. over NW. slope.</p> <p>20.04 The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, mountainous. Soil, rocky clay and loam. Timber, fir, hemlock, cedar, yew, madrone, maple, and alder; undergrowth, vine maple, hazel, arrowwood, salal, Oregon grape, rhododendron, blackberry, and fern.</p> <hr style="width: 100%;"/> <p>From the cor. fo secs. 26, 27, 34, and 35.</p> <p>N. 3° 52' W., bet. secs. 26 and 27.</p>	T 25 S R 2 W	W 1/16 $\frac{S 26}{S 35}$	1973
T 25 S R 2 W				
W 1/16 $\frac{S 26}{S 35}$				
1973				