

# County Surveyor's Record, Douglas County, Oregon

15118

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 2 W., Willamette Meridian, Oregon.

**CHAINS**

Descend 110 ft. over NW. slope. through heavy timber and dense undergrowth.

9.60 Bottom of descent, slopes N. 35° W.; asc. 15 ft. over S. slope.

14.30 Top of ascent, slopes N. 40° W.; desc. 180 ft. over N. slope.

21.85 Point for the S 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

S 1/16  
S 27 | S 26  
1974

from which

A hemlock, 13 ins. diam., bears N. 70° E., 88 lks. dist., mkd. S 1/16 S26 BT.

A hemlock, 24 ins. diam., bears S. 25 1/2° W., 44 1/2 lks. dist., mkd. S 1/16 S27 BT.

Descend 400 ft. over N. slope.

43.70 The 1/4 sec. cor. of secs. 26 and 27, remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap mkd.

1/4  
S 27 | S 26  
1962

from which the original bearing trees

A yew, 13 ins. diam., bears S. 81° E., 32 lks. dist., with healed blaze.

A yew, 10 ins. diam., bears S. 85° W., 38 lks. dist., with healed blaze.

and a bearing tree mkd. by Brooks.

A fir, 43 ins. diam., bears S. 19 1/2° W., 41 lks. dist., with healed blaze.

N. 0° 45' E., beginning new measurement.

Descend 250 ft. over N. slope, through heavy timber and dense undergrowth.

9.80 Creek, 1 lk. wide, course N. 15° W.; desc. 130 ft. over NE. slope.

15.90 Enter creek, 2 lks. wide course N. from S. 30° E.; desc. 40 ft. over NW. slope along creek.

19.95 Leave creek, course N. 15° W.; desc. 180 ft. over N. slope.