

County Surveyor's Record, Douglas County, Oregon

15120

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

40.50

The 1/4 sec. cor. of secs. 23 and 26, remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 23}{S\ 26}$
T 25 S R 2 W
1962

from which the original bearing trees

A hemlock, 27 ins. diam., bears N. 56 1/2° E., 56 lks. dist., with healed blaze.

A hemlock, 15 ins. diam., bears S. 25° E., 31 lks. dist., with scribe mark 4 visible on opened blaze.

and a bearing tree mkd. by Brooks.

A hemlock, 28 ins. diam., bears S. 3° E., 70 lks. dist., with scribe marks 1/4 S26 B visible on open blaze.

S. 89° 30' W., beginning new measurement.

Descend 10 ft. over NW. slope. through heavy timber and dense undergrowth.

0.20 Creek, 1 lk. wide, course N. 40° W.; asc. 60 ft. over NE. slope.

9.15 Top of ascent, slopes N.; desc. 525 ft. over broken W. slope.

39.55 Gravelled road, 15 lks. wide, bears N. 10° E. and South.

40.61 The cor. of secs. 22, 23, 26, and 27.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, yew, cedar, pine, maple, and madrone; undergrowth, salal, hazel, rhododendron, arrowwood, vine maple, poison oak, and fern.

From the cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by G. Robert Lecklider, RLS No. 362. in 1960 and remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, alongside, of which is the original basalt stone, 18 x 9 x 9 ins., firmly set, with 1 notch on S. and 3 notches on E. face, with brass cap mkd.

T 25 S R 2 W
 $\frac{S\ 28\ | S\ 27}{S\ 33\ | S\ 34}$
1962

from which bearing trees mkd. by Lecklider

A white pine, 20 ins. diam., bears N. 87 1/2° E., 181 lks. dist., with healed double blaze.

A fir, 17 ins. diam., bears S. 21° E., 80 1/2 lks. dist., with healed double blaze.