

County Surveyor's Record, Douglas County, Oregon

15121

Dependent Resurvey, Portion of Subdivisional Lines,

T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A fir, 22 ins. diam., bears S. 72 1/2° W., 71 lks. dist., with healed double blaze.

A fir, 10 ins. diam., bears N. 10 1/4° W., 34 lks. dist., with healed double blaze.

S. 1° 03' W., bet. secs. 33 and 34.

Descend 145 ft. over broken SW. slope. through heavy timber and light undergrowth.

19.10 Creek, 2 lks. wide, course W.; asc. 290 ft. over NW. slope.

36.15 Top of ascent, slopes W.; desc. 40 ft. along W. slope.

39.91 The 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by G. Robert Lecklider, RLS No. 362, in 1960, and remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, alongside of which is the original basalt stone, 16 x 12 x 6 ins., firmly set, mkd. 1/4 on W. face, with brass cap mkd.

1/4
S 33 | S 34
T 25 S R 2 W
1962

from which the remains of the original bearing trees

A fir, 47 ins. diam., bears N. 64° E., 75 1/2 lks. dist., with healed blaze.

A root hole, bears S. 53° W., 50 lks. dist, with a down fir alongside, 16 ins. diam., with healed blaze.

and bearing trees mkd. by Lecklider

A fir, 18 ins. diam., bears S. 38 1/2° E., 20 1/2 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 23° W., 22 lks. dist., with healed blaze.

S. 0° 23' W., beginning new measurement.

Ascend 235 ft. over NW. slope. through scattered timber and moderate undergrowth.

7.35 Top of ascent, slopes W.; desc. 80 ft. over SW. slope.

15.40 Ravine, drains. W.; asc. 125 ft. over N. slope.

20.98 Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16
S 33 | S 34
1974

from which