

# County Surveyor's Record, Douglas County, Oregon

~~15404~~  
15122

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 2 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 12 ins. diam., bears N. 81 1/4° E., 29 lks.  
dist., mkd. S 1/16 S34 BT.

A fir, 10 ins. diam., bears N. 48 1/4° W., 28 1/2 lks.  
dist., mkd. S 1/16 S33 BT.

From this point, an iron pin, 1/2 in. diam., firmly set,  
protruding 10 ins. above ground, bears S. 11° E., 0.18  
chs. dist., from which locally established bearing  
trees:

A fir, 13 ins. diam., bears N. 35° E., 2 lks.  
dist., with healed blaze.

A fir, 25 ins. diam., bears S. 44° W., 25 lks.  
dist., with healed blaze.

Ascend 155 ft. over N. slope.

39.17 The original closing cor. of secs. 33 and 34, perpetuated  
and recorded by G. Robert Lecklider, RLS No. 362, in  
1960, monumented with the original basalt stone, 18 x 10  
x 6 ins. firmly set, in a mound of stone, 2 ft. base,  
1 ft. high, mkd. CC on N., 3 notches on W., and 3 notches  
on E. face, from which bearing trees mkd. by Lecklider:

A fir, 17 ins. diam., bears N. 12° E., 26 1/2 lks.  
dist., with healed blaze.

A fir, 13 ins. diam., bears N. 15° W., 16 lks.  
dist., with healed blaze.

I add marks AM to stone. *(circled stamp)*

Ascend 10 ft. over N. slope,

40.63 Intersect the N. bdy. of sec. 4, T. 26 S., R. 2 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

C C  
T 25 S R 2 W  
S 33 | S 34  
S 4  
T 26 S R 2 W  
1974

from which

A fir, 14 ins. diam., bears N. 42 3/4° E., 17 lks.  
dist., mkd. T25S R2W S34 CC BT.

A fir, 14 ins. diam., bears N. 40° W., 50 lks.  
dist., mkd. T25S R 2W S33 CC BT.

From this point, the cor. of secs. 3 and 4 only, T. 26 S.  
R. 2 W., bears S. 89° 26' E., 8.05 chs. dist., herein-  
before scribed.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, hemlock, alder, madrone, chinquapin,  
maple, and yew; undergrowth, vine maple, hazel, arrow-  
wood, salal, Oregon grape, poison oak, and fern.