

County Surveyor's Record, Douglas County, Oregon

15123

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 26, 27, 34, and 35.

N. 88° 17' W., bet. secs. 27 and 34.

Descend 735 ft. over NW. slope, through light timber and undergrowth.

40.15 Creek, 1 lk. wide, course N.; desc. 5 ft. over NW. slope.

40.33 The 1/4 sec. cor. of secs. 27 and 34, perpetuated and recorded by G. Robert Lecklider, RLS No. 362, in 1960, and remonumented by Floyd A. Brooks, in 1962, with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, alongside of which is the original basalt stone, 12 x 10 x 8 ins. firmly set, mkd. 1/4 on N. face, with brass cap mkd.

$$\frac{1/4 \text{ S } 27}{\text{S } 34}$$
 T 25 S R 2 W
 1962

from which a bearing tree mkd. by Lecklider

A cedar, 22 ins. diam., bears S. 75° W., 17 lks. dist., with fragmentary scribe marks visible on open blaze.

and a new bearing tree

A fir, 17 ins. diam., bears N. 51 1/2° W., 93 1/2 lks. dist., mkd. 1/4 S27 BT.

N. 88° 50' W., beginning new measurement.

Descend 205 ft. over NW. slope, through moderate timber and light undergrowth.

20.08 The W 1/16 sec. cor. of sec. 27 and 34, monumented with an unrecorded iron pipe, 24 ins. long, 1/2 in. diam., from which bearing trees of no record.

A fir, 33 ins. diam., bears S. 71 1/2° E., 5 lks. dist., with healed double blaze.

A fir, 22 ins. diam., bears S. 69° W., 41 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{\text{W } 1/16 \text{ S } 27}{\text{S } 34}$$
 1974

from which a new bearing tree

A fir, 11 ins. diam., bears N. 77 1/2° E., 54 lks. dist., mkd. S 1/16 S27 BT.

Deposit iron pipe alongside iron post.

N. 88° 50' W., beginning new measurement.