

County Surveyor's Record, Douglas County, Oregon

15124

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

Descend 185 ft. over general W. slope, through heavy timber and dense undergrowth.

12.15 Creek, 1 lk. wide, course S. 35° W.; asc. 25 ft. over SW. slope.

20.08 The cor. of secs. 27, 28, 33, and 34.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, pine, hemlock, yew, chinquapin, cedar, maple, and madrone; undergrowth, salal, hazel, rhodohendron, vine maple, poison oak, Oregon grape, and fern.

From the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, in a mound of stone, formed from the shattered corner stone, no marks visible, 3 ft. base, to top, with brass cap mkd.

T 25 S	R 2 W
S 29	S 28
S 32	S 33
1962	

from which the remaining original bearing trees

A root hole, bears N. 31° E., 28 lks. dist., with a down and decayed pine alongside, 12 ins. diam., no marks visible.

A fir, 65 ins. diam., bears S. 29° W., 32 lks. dist., no marks visible on opened blaze.

and a bearing tree and bearing object mkd. by Brooks, in 1962

The west face of a rock outcrop, bears N. 80° E., 3 1/2 lks. dist., with marks X BO scratched on rock.

A hemlock, 24 ins. diam., bears N. 21° W., 38 1/2 lks. dist., with healed blaze.

S. 1° 25' E., bet. secs. 32 and 33.

Aseend 55 ft. over N. slope. across logged area, through light undergrowth, marking and blazing the true line.

3.10 Spur, slopes N. 85° W.; desc. 125 ft. over SW. slope.

12.10 Conley Creek, 30 lks. wide, course N. 30° W.; asc. 585 ft. over N. slope. through heavy timber and dense undergrowth.

41.57 The 1/4 sec. cor. of secs. 32 and 33, re-established at proportionate measurement by V. W. Hosford, RLS No. 253, in 1960, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, from which bearing trees mkd. by Hosford:

A fir, 35 ins. diam., bears S. 36° E., 48 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 46° W., 20 lks. dist., with healed blaze.

At the corner point