

# County Surveyor's Record, Douglas County, Oregon

15125

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 2 W., Willamette Meridian, Oregon

**CHAINS**

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 2 W  
1/4  
S 32 | S 33  
1972

Deposit the iron pipe alongside the iron post.

---

S. 1° 25' E., beginning new measurement.

Ascend 225 ft. over N. slope, through heavy timber and light undergrowth.

11.30 Spur, slopes N. 65° E.; desc. 155 ft. over SE. slope.

20.79 The S 1/16 sec. cor. of secs. 32 and 33, established by V. W. Hosford, RLS No. 253, in 1960, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, from which bearing trees mkd. by Hosford:

A fir, 14 ins. diam., bears S. 69° E., 56 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 23° W., 28 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16  
S 32 | S 33  
1972

Deposit the iron pipe alongside the iron post.

---

S 1° 25' E., beginning new measurement.

Descend 165 ft. over SE. slope.

7.60 Dry creek, 5 lks. wide, drains N. 50° E.; asc. 330 ft. over NE. slope.

17.70 The closing cor. of secs. 32 and 33, T. 25 S., R. 2 W.

From this point, the cor. of secs. 4 and 5 only, T. 26 S., R. 2 W., bears N. 89° 15' E., 6.17 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, yew, maple, chinquapin, dogwood, and madrone; undergrowth, vine maple, hazel, rhododendron, manzanita, salal, fern.

From the cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.