

County Surveyor's Record, Douglas County, Oregon

15126

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 2 W
S 30 | S 29
S 31 | S 32
1962

from which the remains of the original bearing trees

A chinquapin snag, 18 ins. diam., bears N. 36° E.,
36 lks. dist., no marks visible.

A chinquapin snag, 15 ins. diam., bears S. 44 1/2° E.,
33 lks. dist., no marks visible.

A root hole, bears S. 13° W., 41 lks. dist., with
a down chinquapin alongside, 16 ins. diam., with
healed blaze.

A fir, 25 ins. diam., bears N. 12 1/2° W., 51 lks.
dist., healed blaze.

and a bearing tree mkd. by Brooks, in 1962

A fir, 24 ins. diam., bears N. 78° E., 21 lks.
dist., with healed blaze.

and new bearing trees

A hemlock, 15 ins. diam., bears S. 3° E., 55 lks.
dist., mkd. T25S R2W S32 BT.

A fir, 15 ins. diam., bears S. 17° W., 94 lks.
dist., mkd. T25S R2W S31 BT.

S. 0° 07' W., bet. secs. 31 and 32.

Ascend 380 ft. over NW. slope, through heavy timber and
light undergrowth.

21.60 Spur, slopes N. 70° W.; desc. 315 ft. over S. slope.

40.22 The 1/4 sec. cor. of secs. 31 and 32, monumented with an
iron post, 2 1/2 ins. diam., firmly set, in a mound of
stone, 2 1/2 ft. base, to top, with brass cap mkd.

1/4
S 31 | S 32
T 25 S R 2 W
1962

from which the original bearing trees

A fir, 24 ins. diam., bears S. 60° E., 35 lks.
dist., with healed blaze.

A white pine, 53 ins. diam., bears N. 40° W.,
10 lks. dist., with healed blaze.

and a bearing tree mkd. by Brooks, in 1962

A fir, 13 ins. diam., bears N. 88 1/4° E., 85 lks.
dist., with healed blaze.

S. 2° 12' W., beginning new measurement.

Descend 275 ft. over SW. slope, through heavy timber
and dense undergrowth.