

County Surveyor's Record, Douglas County, Oregon

15127

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

- 8.90 Creek, 5 lks. wide, course N. 50° W.; asc. 120 ft. over N. slope.

- 22.52 Point for the S 1/16 sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
 S 31 | S 32
 1972

 from which

A hemlock, 7 ins. diam., bears S. 83° E., 68 lks. dist., mkd. S 1/16 S32 BT.

 A hemlock, 18 ins. diam., bears N. 32 1/2° W., 48 lks. dist., mkd. S 1/16 S31 BT.

 Ascend 50 ft. over N. slope.

- 23.75 Creek, 2 lks. wide, course N. 70° E.; asc. 665 ft. over steep N. slope.

- 41.33 The closing cor. of secs. 31 and 32, T. 25 S., R. 2 W.

From this point, the cor. of secs. 5 and 6 only, T. 26 S., R. 2 W., bears N. 89° 31' E., 7.54 chs. dist., hereinbefore described.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, maple, chinquapin, yew, and dogwood; undergrowth, vine maple, hazel, rhododendron, salal, and fern.

- From the cor. of secs. 28, 29, 32, and 33.

N. 89° 32' W., bet. secs. 29 and 32.

Descend 240 ft. over SW. slope, through scattering timber and dense undergrowth.

- 10.85 Creek, 3 lks. wide, course S. 65° W.; asc. 135 ft. over SE. slope.

- 27.60 Spur, slopes S.; desc. 90 ft. over SW. slope.

- 40.02 The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

1/4 $\frac{S\ 29}{S\ 32}$
 T 25 S R 2 W
 1962

 from which the original bearing trees

A fir, 37 ins. diam., bears N. 18° W., 112 lks. dist., with healed blaze.

 A fir, 35 ins. diam., bears S. 43° E., 12 lks. dist., with healed blaze.

 N. 89° 40' W., beginning new measurement.