

County Surveyor's Record, Douglas County, Oregon

15128

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

Descend 220 ft. over SW. slope, through scattering timber and light undergrowth.

14.55 Conley Creek, 10 lks. wide, course N. 50° W.; 75 ft. over NE. slope.

20.00 Point for the W 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 29}{S\ 32}$
1972

from which

A fir, 4 ins. diam., bears N. 71° E., 14 lks. dist., mkd. X BT.

A hemlock, 10 ins. diam., bears S. 22° W., 33 lks. dist., mkd. W 1/16 S32 BT.

Ascend 275 ft. over NE. slope.

40.00 The cor. of secs. 29, 30, 31, and 32.

The corner point is located on top of spur, slopes N. 20° W.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, madrone, chinquapin, and dogwood; undergrowth, vine, maple, hazel, rhododendron, salal, fern, and Oregon grape.

N. 88° 41' W., bet. secs. 30 and 31.

Descend 50 ft. over NW. slope, through heavy timber and dense undergrowth.

4.45 Ravine, drains. N.; asc. 20 ft. over NE. slope.

8.85 Spur, slopes N.; desc. 325 ft. over NW. slope.

23.25 Ravine, drains. N.; 25 ft. over NE. slope.

39.95 The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 3 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 30}{S\ 31}$
T 25 S R 2 W
1962

from which the remaining original bearing tree

A white fir, 40 ins. diam., bears S. 20° W., 62 lks. dist., with scribe marks BT visible on partially opened blaze.

and bearing trees mkd. by Brooks, in 1962

A cottonwood, 20 ins. diam., bears N. 7 1/2° W., 62 lks. dist., with healed blaze.