

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 25 S., R. 2 W.,
Willamette Meridian, Oregon.

15130

CHAINS	Subdivision of Section 31, T. 25 S., R. 2 W., Willamette Meridian, Oregon
	<p>From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.</p> <p>N. 1° 03' E., on the N. S. center line of sec. 31.</p> <p>Ascend 35 ft. over SW. slope, through heavy timber and light undergrowth, marking and blazing the true line.</p>
3.20	Spur, slopes N. 10° W.; desc. 310 ft. over NW. slope.
13.70	Creek, 3 lks. wide, course N. 50° W.; desc. 415 ft. over NW. slope.
28.40	Creek, 3 lks. wide, course N. 40° W.; desc. 215 ft. over broken NW. slope.
42.28	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 25 S R 2 W C 1/4 S 31 1972</p>
	from which
	A hemlock, 7 ins. diam., bears N. 42° E., 48 lks. dist., mkd. C 1/4 S31 BT.
	A hemlock, 40 ins. diam., bears S. 54° W., 46 lks. dist., mkd. C 1/4 S31 BT.
	Descend 55 ft. over NW. slope.
45.80	Creek, 6 lks. wide, course N. 80° W.; asc. 175 ft. over SW. slope.
58.45	Spur, slopes W.; desc. 30 ft. over NW. slope.
59.90	Creek, 2 lks. wide, course W.; asc. 130 ft. over SW. slope.
72.30	Spur, slopes N. 85° W.; desc. 290 ft. over NW. slope.
82.78	The 1/4 sec. cor. of secs. 30 and 31.
	<p>From the 1/4 sec. cor of secs. 31 and 32.</p> <p>N. 89° 05' W., on the E. and W. center line of sec. 31.</p> <p>Descend 520 ft. over broken SW. slope, through heavy timber and dense undergrowth.</p>
31.95	Creek, 6 lks. wide, course N. 70° W.; asc. 45 ft. over NE. slope.
36.60	Top of ascent, slopes N.; desc. 10 ft. over NW. slope.
40.66	The center 1/4 sec. cor. of sec. 31.