

# County Surveyor's Record, Douglas County, Oregon

**15133**

Subdivision of Section 32, T. 25 S., R. 2 W.,  
Willamette Meridian, Oregon

CHAINS	Descend 35 ft. over gradual NW. slope.
2.75	Ravine, drains. N. 28° E.; desc. 60 ft. over NE. slope.
7.35	Ravine, drains. N. 70° E.; asc. 15 ft. over SE. slope.
9.00	Spur, slopes N. 68° E.; desc. 170 ft. over NE. slope.
17.60	Spur, slopes N. 22° E.; desc. 375 ft. over N. slope.
37.10	Conley Creek, 20 lks. wide, course N. 76° W.; asc. 135 ft. over S. slope.
41.00	The 1/4 sec. cor. of secs. 29 and 32.
From the 1/4 sec. cor. of secs. 32 and 33.	
N. 88° 36' W., on the E. and W. center line of sec. 32.	
Ascend 80 ft. over NE. slope, through heavy timber and dense undergrowth.	
2.55	Spur, slopes N.; desc. 130 ft. over NW. slope.
9.90	Spur, slopes N. 28° W.; desc. 275 ft. over W. slope.
19.35	Creek, 5 lks. wide, course N. 30° W.; asc. 5 ft. over NE. slope.
20.48	Point for the center E 1/16 sec. cor. of sec. 32.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.	
$\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{S } 32 \quad \text{C} \\ 1975 \end{array}$	
from which	
A cedar, 10 ins. diam., bears S. 8° W., 13 1/2 lks. dist., mkd. CE 1/16 S32 BT.	
A hemlock, 13 ins. diam., bears N. 7 3/4° E., 82 lks. dist., mkd. CE 1/16 S32 BT.	
Ascend 50 ft. over NE. slope.	
25.60	Spur, slopes N. 6° W.; desc. 105 ft. over NW. slope.
28.80	Creek, 5 lks. wide, course N. 12° W.; asc. 55 ft. over NE. slope.
32.85	Spur, slopes N.; desc. 35 ft. over NW. slope.
36.10	Creek, 3 lks. wide, course N. 40° E.; asc. 80 ft. over NE. slope.
40.96	The center 1/4 sec. cor. of sec. 32.
N. 88° 36' W., beginning new measurement.	
Ascend 45 ft. over NE. slope.	
2.25	Spur, slopes N. 10° W.; desc. 25 ft. over NW. slope.