

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 32, T. 25 S., R. 2 W.,  
Willamette Meridian, Oregon

15124

**CHAINS**

- 5.65 Ravine, drains N.; asc. 110 ft. over NE. slope.
- 11.25 Spur, slopes NW.; desc. 110 ft. over NW. slope.
- 15.90 Ravine, drains. N.; asc. 50 ft. over NE. slope.
- 20.09 Point for the center W 1/16 sec. cor. of sec. 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

C  $\frac{W \ 1/16}{S \ 32}$  C  
1975

from which

A hemlock, 11 ins. diam., bears S. 44° E., 52 1/2 lks. dist., mkd. CW 1/16 S32 BT.

A fir, 8 ins. diam., bears N. 70 1/4° W., 26 lks. dist., mkd. CW 1/16 S32 BT.

Corner is located on a spur, slopes N.

Descend 85 ft. over NW. slope.

- 28.05 Ravine, drains. N.; asc. 25 ft. over NE. slope.
- 29.30 Ridge, bears N. 10° W. and S. 10° E.; desc. 295 ft. over SW. slope.
- 40.18 The 1/4 sec. cor. of secs. 31 and 32.

From the E 1/16 sec. cor. of sec. 32 only, on the S. bdy. of the Tp.

N. 0° 50' W., on the N. and S. center line of the SE 1/4 of sec. 32.

Descend 30 ft. over E. slope, through heavy timber and dense undergrowth.

- 3.95 Ravine, drains. S. 80° E.; asc. 40 ft. over SE. slope.
- 10.85 Spur, slopes NE.; desc. 70 ft. over N. slope.
- 13.15 Edge of rock bluff, edge bears E. and W.; desc. 100 ft. over N. slope.
- 13.20 Base of rock bluff; desc. 110 ft. over NE. slope.
- 18.02 Point for the SE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SE 1/4.

Set an iron post, 28 ins. long, 2 1/12 ins. diam., 20 ins. in the ground, with brass cap mkd.

SE 1/16 S 32  
1975

from which

A hemlock, 8 ins. diam., bears N. 47° W., 88 lks. dist., mkd. SE 1/16 S32 BT.