

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 32, T. 25 S., R. 2 W.,
Willamette Meridian, Oregon

15136

CHAINS

11.35	Spur, slopes SW.; desc. 20 ft. over NW. slope.
13.25	Ravine, drains. W.; asc. 25 ft. over SW. slope.
18.56	<p>Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S32 1975</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears S. 11° E., 29 lks. dist., mkd. SW 1/16 S32 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 63° W., 65 lks. dist., mkd. SW 1/16 S32 BT.</p> <p>Ascend 5 ft. over SW. slope.</p>
19.00	Spur, slopes S. 76° W., deesc. 60 ft. over NW. slope.
22.80	Ravine, drains. S. 88° W.; asc. 355 ft. over SW. slope.
35.15	Top of ridge, bears E. and W.; desc. 205 ft. over NE. slope.
40.67	The center W 1/16 sec. cor. of sec. 32.
From the center S 1/16 sec. cor. of sec. 32.	
N. 89° 46' W., on the E. and W. center line of the SW 1/4 of sec. 32.	
Ascend 30 ft. over NE. slope, through heavy timber and dense undergrowth.	
1.25	Ridge top, bears N. 20° W., desc. 65 ft. over SW. slope.
3.65	Ravine, drains. S. 18° W.; desc. 5 ft. over SW. slope.
5.55	Ravine, drains. S. 10° E.; asc. 25 ft. over SE. slope.
7.80	Spur, slopes W.; desc. 400 ft. over W. slope.
20.52	The SW 1/16 sec. cor. of sec. 32.
22.00	Spur, slopes S. 55° W.; desc. 255 ft. over NW. slope.
31.60	Bottom of descent, slopes S.; desc. 5 ft. over nearly level land.
33.35	Begin descent, 120 ft. over broken SW. slope.
39.65	Creek, 18 lks. wide, course N. 58° W.; asc. 10 ft. over NE. slope.
40.40	Spur, slopes N.; desc. 10 ft. over NW. slope.
40.69	Creek, 3 lks. wide, course N. 16° E.; asc. 15 ft. over NE. slope.
41.04	The S 1/16 sec. cor. of secs. 31 and 32.