

# County Surveyor's Record, Douglas County, Oregon

15140

Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which the remains. of the original bearing trees

A root crown, bears N. 24° W., 116 lks. dist., with a down pine alongside, 23 ins. diam., with fragmentary scribe marks visible on partially opened blaze. (Record, N. 35° W., 120 lks.)

and bearing trees mkd. by Evans

A pine, 22 ins. diam., bears N. 19° E., 72 lks. dist., with healed blaze.

A pine, 23 ins. diam., bears S. 9° E., 13 lks. dist., with fragmentary scribe marks visible on partially open blaze.

A pine, 15 ins. diam., bears S. 45 3/4° W., 49 lks. dist., with fragmentary scribe marks visible on partially open blaze.

A pine, 16 ins. diam., bears N. 49 1/4° W., 23 lks. dist., with fragmentary scribe marks visible on partially open blaze.


and a bearing tree mkd. by Byron

A fir, 12 ins. diam., bears S. 26 1/2° W., 99 lks. dist., with fragmentary scribe marks visible on partially open blaze.

N. 0° 12' E., bet. secs. 25 and 30, marking and blazing the true line.

Ascend 30 ft. over SE. slope, through scattering timber and moderate undergrowth.

- 1.45 Spur, slopes E.; desc. 40 ft. over NE. slope.
- 3.35 Ravine, drains. E.; asc. 190 ft. over SE. slope.
- 10.80 Spur, slopes E.; desc. 170 ft. over broken NE. slope.
- 17.55 Ravine, drains. S. 65° E.; asc. 245 ft. over SW. slope.
- 24.75 Spur, slopes S. 70° E.; desc. 120 ft. over NE. slope.
- 31.60 Bottom of descent, slopes E.; asc. 230 ft. over SE. slope.
- 37.40 Creek, 4 lks. wide, course N. 60° E.; asc. 55 ft. over SE. slope.
- 39.68 The 1/4 sec. cor. of secs. 25 and 30, reestablished by Arthur R. Evans, Registered Mining Engineer, No. 2741, in 1953, and subsequently perpetuated by James W. Byron, Deputy County Surveyor, in 1963. This position is harmoniously related to existing original corners, has been recognized as the corner by adjacent landowners, and is accepted as the best available evidence of the original corner position. The corner is monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Evans