

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 30 S., R. 7 W.,
Willamette Meridian, Oregon

15142

CHAINS

A pine, 17 ins. diam., bears S. 78° E., 60 lks. dist., with healed blaze, and scribe marks BT visible on bark blaze.

A pine, 18 ins. diam., bears N. 85° W.; 76 lks. dist., with healed blaze, and scribe marks BT visible on bark blaze.

and a bearing tree mkd. by Byron

A pine, 23 ins. diam., bears S. 40° E., 36 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, maple, oak, cedar, chinquapin, and hemlock; undergrowth, salal, hazel, poison oak, and Oregon grape.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., perpetuated and recorded by Howard W. Johnstone, for Roseburg Lumber Co., in 1962, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:

A black oak snag, 23 ins. diam., bears N. 70° E., 70 lks. dist., with partially opened blaze.

A black oak, 15 ins. diam., bears S. 50° E., 122 lks. dist., with partially opened blaze.

A black oak, 25 ins. diam., bears S. 60° W., 327 lks. dist., with partially opened blaze.

and bearing trees mkd. by Johnstone

A root hole, bears N. 51 1/2° E., 76 lks. dist., with a down fir, alongside, 12 ins. diam., with partially healed double blaze.

A pine, 20 ins. diam., bears S. 28° W., 88 1/2 lks. dist., with partially healed double blaze.

A pine, 25 ins. diam., bears N. 51° W., 5 1/2 lks. dist., with scribe marks T30S R7W S13 BT visible on partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.

T 30 S	
R 7 W	R 6 W
S 13	S 18
S 24	S 19
1973	

from which a new bearing tree

A fir, 15 ins. diam., bears N. 13 1/2° E., 156 lks. dist., mkd. T30S R7W S18 BT.

N.0° 12' E., bet. secs. 13 and 18.