

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 30 S., R. 7 W.,
Willamette Meridian, Oregon

15144

CHAINS

A root hole, bears S. 23° W., 27 lks. dist., with a down fir alongside, 30 ins. diam., with healed double blaze.

A fir, 8 ins. diam., bears N. 18° W., 65 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 25° W., 53 lks. dist., mkd. T30S R7W S13 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, pine, white fir, maple, alder, yew, and madrone; undergrowth, fern, blackberry, Oregon grape, hazel, poison oak, and vine maple.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., willamette Meridian, Oregon.

(Restoring the 1872 survey by William H. Byars,
U. S. Deputy Surveyor)

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., marking and blazing the true line.

N. 88° 14' W., bet. secs. 25 and 36.

Ascend 315 ft. over E. slope. through scattering timber and moderate undergrowth.

11.80 Ridge, bears N. 60° W., and S. 60° E.; desc. 65 ft. over broken SW. slope.

21.54 Point for the E 1/16 sec. cor. of secs. 25 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

E 1/16 $\frac{S\ 25}{S\ 36}$
1971

from which

A pine, 21 ins. diam., bears N. 46° W., 32 lks. dist., mkd. E 1/16 S25 BT.

A pine, 16 ins. diam., bears S. 59° W., 42 lks. dist., mkd. E 1/16 S36 BT.

Descend 220 ft. over broken SW. slope.

29.70 Creek, 2 lks. wide, course S. 50° W.; asc. 130 ft. over SE. slope.

43.08 The 1/4 sec. cor. of secs. 25 and 36, perpetuated and recorded by Arthur R. Evans, Registered Mining Engineer No. 2741, in 1953, and subsequently perpetuated by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pin, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which the remaining original bearing tree: