

County Surveyor's Record, Douglas County, Oregon

15145

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A laurel, 35 ins. diam., bears N. 28° W., 218 lks. dist., with fragmentary scribe marks visible on decayed blaze.

and a bearing tree mkd. by Evans

A pine, 18 ins. diam., bears S. 10° W., 5 1/2 lks. dist., with fragmentary scribe marks visible on partially open blaze.

and a bearing tree mkd. by Byron

A fir, 6 ins. diam., bears N. 60 3/4° W., 15 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

FD. OK BY SMALLEY 7/92 1/4 S 25
M 112-52 S 36
T 30 S R 7 W
1971

Deposit the iron pin alongside the iron post.

S. 89° 48' W., beginning new measurement.

Ascend 20 ft. over SE. slope.

- 1.30 Dirt road, 20 lks. wide, bears N. 50° E., and S. 50° W.
- 4.40 Top of ascent, slopes SW.; desc. 260 ft. over NW. slope.
- 18.30 Ravine, drains S. 30° W.; asc. 100 ft. over broken SW. slope.
- 27.05 Ridge, bears N. 50° E., and S. 50° W.; desc. 700 ft. over precipitous NW. slope.

43.28 The cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by Arthur R. Evans, Registered Mining Engineer No. 2741, in 1953, and subsequently perpetuated by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.

T 30 S
S 26 | S 25
S 35 | S 36
R 7
1964

from which the only remaining original bearing tree

A fir, 34 ins. diam., bears N. 76° W., 72 lks. dist., with healed blaze. (Record, N. 80° W.)

and bearing trees mkd. by Evans

An oak, 10 ins. diam., bears N. 21° E., 15 lks. dist., with scribe marks T30S R7W S25 BT visible on open blaze.