

# County Surveyor's Record, Douglas County, Oregon

15146

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

An oak, 9 ins. diam., bears S. 64° E., 18 lks.  
dist., with scribe marks R7W S36 BT visible  
on partially open blaze.

An oak, 8 ins. diam., bears S. 2° E., 25 lks.  
dist., with scribe marks T30S R7W S35 visible on  
partially open blaze.

and a new bearing tree

An oak, 10 ins. diam., bears S. 11 1/2° W., 35 lks.  
dist., mkd. T30S R7W S35 BT.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, cedar, hemlock, oak, maple, alder,  
and chinquapin; undergrowth, salal, hazel, rhododendron,  
poison oak, and Oregon grape.

N. 1° 20' E., bet. secs. 25 and 26.

Descend 80 ft. over broken NW. slope.

6.05 Creek, 4 lks. wide, course S. 60° W.; asc. 200 ft. over  
broken SW. slope.

19.86 Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, and in a mound of stone, 2 ft. base,  
to top, with brass cap mkd.

S 1/16  
S 26 | S25  
1971

from which

A pine, 21 ins. diam., bears S. 66° E., 49 lks.  
dist., mkd. S 1/16 S25 BT.

A pine, 11 ins. diam., bears S. 39 3/4° W., 7 lks.  
dist., mkd. S 1/16 S26 BT.

Ascend 150 ft. over broken SW. slope.

28.25 Top of ascent, slopes W.; desc. 25 ft. over NW. slope.

33.55 Salt Creek, 10 lks. wide, course S. 50° W.; asc. 50 ft.  
over broken SE. slope.

34.75 Creek, 2 lks. wide, course SE.; asc. 50 ft. over broken  
SE. slope.

39.72 The 1/4 sec. cor. of secs. 25 and 26, determined at  
record bearing and distance from the remains of the  
original bearing trees:

A pine stump, 24 ins. diam., bears N. 55° W.,  
77 lks. dist., with fragmentary scribe marks  
visible on partially opened blaze.

At the corner point

Set an iron psot, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, and in a mound of stone, 3 ft. base,  
to top, with brass cap mkd.