

County Surveyor's Record, Douglas County, Oregon

15148

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 15 ins. diam., bears S. $31\ 1/2^\circ$ E., 76 1/2 lks. dist., mkd. T30S R7W S25 BT.

A white fir, 8 ins. diam., bears S. 5° W., 73 1/2 lks. dist., mkd. T30S R7W S26 BT.

A white fir, 10 ins. diam., bears N. $15\ 3/4^\circ$ W., 44 lks. dist., mkd. T30S R7W S23 BT.

Deposit the iron pipe alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, hemlock, cedar, maple, oak, alder, and chinquapin; undergrowth, salal, hazel, rhododendron, Oregon grape, and poison oak.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.

N. $87^\circ\ 59'$ W., bet. secs. 24 and 25.

Ascend 185 ft. over broken E. slope.

12.75 Ridge, bears N. 55° E., and S. 55° W.; asc. 45 ft. over broken NE. slope.

18.50 Spur, slopes N.; desc. 80 ft. over NW. slope.

24.55 Ravine, drains N. 20° W.; asc. 125 ft. over broken NE. slope.

30.15 Top of ascent, slopes N.; desc. 255 ft. over broken NW. slope.

42.02 The 1/4 sec. cor. of secs. 24 and 25, perpetuated and recorded by John H. Markham, Jr., Registered Logging Engineer No. 2880, in 1951, and subsequently perpetuated by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:

A sawed pine stump, 44 ins. diam., bears N. 32° E., 30 lks. dist., with scribe marks 1/4 BT visible on opened blaze. (Record, N. 20° E., 22 lks.)

A pine snag, 26 ins. diam., bears S. 30° W., 31 lks. dist., with fragmentary scribe marks visible on decayed blaze.

and a bearing tree mkd. by Byron

A laurel, 18 ins. diam., bears North, 54 lks. dist., with scribe marks 1/4 S24 CS visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.