

# County Surveyor's Record, Douglas County, Oregon

**15149**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

1/4  $\frac{S\ 24}{S\ 25}$   
T 30 S R 7 W  
1971

from which a new bearing tree

A fir, 4 ins. diam., bears S. 65° W., 13 lks.  
dist., mkd. 1/4 S25 BT.

Deposit the iron pipe alongside the iron post.

S 88° 37' W., beginning new measurement.

Descend 175 ft. over broken NW. slope.

- 5.60 Ravine, drains. N. 20° W., asc. 5 ft. over NE. slope.
- 7.10 Spur, slopes N. 20° W., desc. 70 ft. over NW. slope.
- 9.65 Ravine, drains. N. 20° W., asc. 5 ft. over NE. slope.
- 11.05 Spur, slopes N. 15° W.; desc. 280 ft. over NW. slope.
- 13.15 Dirt road, 15 lks. wide, bears N. 25° E., and S. 25° W.
- 30.75 Creek, 10 lks. wide, course S. 10° E.; asc. 80 ft. over broken SE. slope.
- 38.00 Creek, 5 lks. wide, course S. 80° E.; asc. 35 ft. over broken SE. slope.
- 41.30 The cor. of secs. 23, 24, 25, and 26.

Land, mountainous.  
Soil, rocky clay.  
Timber, pine, fir, hemlock, maple, oak, chinquapin, and alder; undergrowth, salal, hazel, poison oak, and Oregon grape.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.

S. 89° 16' W., bet. secs. 12 and 13.

Ascend 275 ft. over SE. slope through heavy timber and moderate undergrowth.

- 7.75 Spur, slopes S. 30° W., desc. 450 ft. over W. slopes; also edge of timber, bears N. and S.
- 20.40 Creek, 2 lks. wide, course S. 25° W., asc. 790 ft. over E. slope.
- 22.90 Dirt road, 15 lks. wide, bears S. 10° W., and N. 25° E.
- 39.41 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 7 W  
1/4  $\frac{S\ 12}{S\ 13}$   
1973