

County Surveyor's Record, Douglas County, Oregon

15150

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

A white fir, 12 ins. diam., bears S. 2° E., 47 lks.
dist., mkd. 1/4 S13 BT.

A cedar, 8 ins. diam., bears N. 81° W., 25 lks.
dist., mkd. 1/4 S12 BT.

Ascend 190 ft. over E. slope; also enter heavy timber
and light undergrowth, edge bears N. and S.

41.00 Enter burned area, edge bears generally N. and S.

50.00 Ridge, bears N. 5° E., and S. 5° W.; desc. 690 ft. over
W. slope.

70.10 Creek, 3 lks. wide, course S. 30° W., asc. 190 ft. over
SE. slope.

78.82 The cor. of secs. 11, 12, 13, and 14, perpetuated and
recorded by Vernon R. Tracy, Deputy County Surveyor, in
1964, monumented with an iron post, 1 in. diam., firmly
set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 30 S R 7 W
S 11 | S 12
S 14 | S 13
1964

from which the remains of the original bearing tree

A burned pine snag, 42 ins. diam., bears S. 70° W.,
14 lks. dist., with burned blaze.

and bearing trees marked by Tracy

A burned fir, 8 ins. diam., bears N. 87° E., 31 lks.
dist., with burned double blaze.

A burned fir, 8 ins. diam., bears S. 15° W., 10
lks. dist., with ~~burned double~~ double blaze.

A burned fir, 13 ins. diam., bears S. 21° E., 25
lks. dist., with burned double blaze.

and a new bearing tree

A burned fir, 15 ins. diam., bears N. 2° E., 17
lks. dist., mkd. T30S R7W S12 BT.

No other trees available within limits

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, pine, white fir, maple, alder, yew,
and madrone; undergrowth, fern blackberry, Oregon grape,
hazel, poison oak, and vine maple.

Subdivision of Section 25, T. 30 S., R. 7 W.,
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 25 and 36.

N. 1° 02' E., on the N. and S. center line of sec. 25,
marking and blazing the true line.