



County Surveyor's Record, Douglas County, Oregon

15151

Subdivision of Section 25, T. 30 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	Ascend 85 ft. over S. slope, through scattering timber and dense undergrowth.
1.55	Dirt road, 20 lks. wide, bears N. 30° E., and S. 30° W.
5.30	Ridge, bears E. & W.; desc. 150 ft. over NW. slope.
12.90	Ravine, drains N. 50° W.; desc. 5 ft. over NW. slope.
14.00	Spur, slopes N. 40° W.; desc. 60 ft. over NW. slope.
17.00	Creek, 5 lks. wide, course N. 35° W.; asc. 5 ft. over SW. slope.
18.60	Spur, slopes S. 85° W.; desc. 25 ft. over NW. slope.
19.51	Point for the center S 1/16 sec. cor. of sec. 25. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	
	from which
	A fir, 19 ins. diam., bears North, 75 lks. dist., mkd. C S 1/16 S25 BT.
	A fir, 8 ins. diam., bears S. 18 1/4° W., 34 lks. dist., mkd. C S 1/16 S25 BT.
	Descend 3 ft. over N. slope.
19.60	Creek, 5 lks. wide, course S. 65° W.; asc. 470 ft. over broken SE. slope.
36.10	Dirt road, 20 lks. wide, bears N. 50° E., and S. 50° W.
39.02	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	
	from which
	A fir, 8 ins. diam., bears S. 61° E., 37 1/2 lks. dist., mkd. C 1/4 S25 BT.
	A fir, 6 ins. diam., bears S. 40° W., 46 lks. dist., mkd. C 1/4 S25 BT.
	Ascend 95 ft. over SE. slope.
45.00	Ridge, bears E. and W.; desc.; 40 ft. over broken NW. slope.
48.30	Bottom of descent, slopes W.; asc. 25 ft. over S. slope.
51.00	Spur, slopes W.; desc. 10 ft. over NW. slope.
53.00	Ravine, drains S. 75° W.; asc. 180 ft. over broken SW.