

# County Surveyor's Record, Douglas County, Oregon

Subdivison of Section 25, T. 30 S., R. 7 W.,  
Willamette Meridian, Oregon

15152

**CHAINS**

- slope.
- 62.80 Spur, slopes S. 35° W.; desc. 75 ft. over NW. slope.
- 66.75 Ravine, drains N. 80° W.; desc. 5 ft. over SW. slope.
- 68.20 Spur, slopes N. 70° W.; desc. 145 ft. over NW. slope.
- 75.60 Creek, 5 lks. wide, course S. 80° W.; asc. 20 ft. over SW. slope.
- 76.85 Spur, slopes S. 85° W.; desc. 55 ft. over NW. slope.
- 79.54 The 1/4 sec. cor. of secs. 24 and 25.

---

From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.

N. 89° 11' W., on the E. and W. center line of sec. 25.

Ascend 85 ft. over SE. slope, through scattering timber and dense undergrowth.

- 6.10 Top of ascent, slopes S.; desc. 10 ft. over SW. slope.
- 7.30 Ravine, drains S.; asc. 230 ft. over SE. slope.
- 12.50 Dirt road, 15 lks. wide, bears N. 35° E., and S. 35° W.
- 17.90 Ridge, bears N. and S.; desc. 80 ft. over W. slope.
- 21.275 Point for the center E 1/16 sec. cor. of sec. 25.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

C  $\frac{E \ 1/16}{S \ 25}$  C  
1971

from which

A fir, 6 ins. diam., bears N. 15° E., 24 1/2 lks. dist., mkd. CE 1/16 S25 BT.

A fir, 25 ins. diam., bears South, 7 1/2 lks. dist., mkd. CE 1/16 S25 BT.

Descend 85 ft. over broken W. slope.

- 21.90 Dirt road, 20 lks. wide, bears N. and S.
- 25.40 Creek, 2 lks. wide, course S. 60° W.; asc. 10 ft over broken E. slope.
- 28.70 Top of ascent, slopes SW.; desc. 40 ft. over W. slope.
- 30.30 Ravine, drains S. 35° W.; asc. 155 ft. over E. slope.
- 37.30 Dirt road, 20 lks. wide, bears N. 40° E., and S. 40° W.
- 42.55 The center 1/4 sec. cor. of sec. 25.
- Ascend 35 ft. over SE. slope.
- 47.50 Ridge, bears N. 10° E., and S. 10° W.; desc. 510 ft. over NW. slope.