

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15158

CHAINS

(Restoring the survey by Dennis Hathorn,
Deputy Surveyor, in 1855,
the retracement by Addison R. and Samuel C. Flint,
Deputy Surveyors, in 1881, and
the retracement by William P. Heydon,
Deputy Surveyor, in 1896)

Beginning at the cor. of secs. 4, 5, 32, and 33, on the
S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins.
diam., firmly set, projecting 4 ins. above ground, with
brass cap mkd.

T 26 S R 7 W
S 32 | S 33
S 5 | S 4
T 27 S
1959

from which the remains of the original bearing trees

A sawed fir stump, 36 ins. diam., bears
N. 75° 3/4° E., 18 lks. dist., no marks visible.

A sawed fir stump, 36 ins. diam., bears East, 78
lks. dist., no marks visible.

A sawed fir stump, 32 ins. diam., bears S. 23° W.,
75 lks. dist., with healed blaze.

A sawed fir stump, 24 ins. diam., bears N. 64° W.,
45 lks. dist., with healed blaze.

and the remains of a bearing tree mkd. by Zirpel and
Martin, in 1959

A sawed fir stump, 28 ins. diam., bears S. 68 1/2° W.,
67 lks. dist., with scribe marks T27S R7W S5 BT.
visible on open blaze.

No suitable trees available within reasonable limits.

S. 89° 21' W., bet. secs. 5 and 32, marking and blazing
the true line.

Ascend 50 ft. over E. slope, through moderate young
timber and moderate undergrowth.

1.90 Bear Ridge, bears N. and S., also Callahan Road, gravell-
ed, 25 lks. wide, bears N. and S.; desc. 90 ft. over NW.
slope.

13,20 Ravine, drains N. 20° W.; asc. 85 ft. over NE. slope.

17.85 Spur, slopes N.; desc. 70 ft. over NW. slope.

20.085 Point for the E 1/16 sec. cor. of secs. 5 and 32.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, 3 ins.
in drill hole, in solid rock, with top mkd.

E 1/16 $\frac{S 32}{S 5}$
1974

from which