

# County Surveyor's Record, Douglas County, Oregon

**15159**

Dependent Resurvey, Portion of South Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 11 ins. diam., bears N. 41 1/2° E., 79 lks.  
dist., mkd. E 1/16 S32 BT.

A fir, 6 ins. diam., bears S. 51 1/2° E., 75 lks.  
dist., mkd. E 1/16 S5 BT.

Descend 400 ft. over NW. slope.

31.70 Bottom of descent, slopes N.; asc. 15 ft. over E. slope.

33.50 Top of ascent, slopes N.; desc. 190 ft. over W. slope.

40.17 The 1/4 sec. cor. of secs. 5 and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 1/4 ins. diam., set in mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 26 S R 7 W  
1/4  $\frac{S\ 32}{S\ 5}$   
1961

from which the remains of the original bearing tree

A sawed fir stump, 36 ins. diam., bears S. 58° E.,  
13 lks. dist., with fragmentary scribe marks  
visible on open blaze.

and new bearing trees

A hemlock, 10 ins. diam., bears N. 19° E., 185  
lks. dist., mkd. 1/4 S32 BT.

A fir, 6 ins. diam., bears S. 10 1/2° W., 46 1/2 lks.  
dist., mkd. 1/4 S5 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, maple, madrone, and cedar; under-  
growth, young timber, salal, hazel, Oregon grape, arrow-  
wood, and fern.

From the cor. of secs. 5, 6, and 31, and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 26 S R 7 W  
 $\frac{S\ 31\ | S\ 32}{S\ 6\ | S\ 5}$   
T 27 S  
1961

from which the remains of the original bearing trees

A sawed fir stump, 28 ins. diam., bears N. 16° E.,  
265 lks. dist., no marks visible.

A sawed fir stump, 42 ins. diam., bears S. 72° W.,  
65 lks. dist., with scribe marks BT visible on  
opened blaze. (Record, S. 75° W.)

and bearing trees mkd. by Byron