

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15160

CHAINS

A sawed fir stump, 21 ins. diam., bears N. 43 1/4° E., 63 lks. dist., no marks visible.

A fir snag, 25 ins. diam., bears S. 9° E., 99 lks. dist., with scribe marks T27S R7W S5 CS BT visible on open blaze.

No suitable trees available within reasonable limits.

S. 89° 30' W., bet. secs. 6 and 31.

Descend 15 ft. over gentle NW. slope. through heavy young timber and moderate undergrowth.

4.30 Dirt road, 15 lks. wide, bears N. 60° W. and S. 75° E., also bottom of descent, slopes NW.; asc. 135 ft. over NE. slope.

11.05 Spur, slopes N.; desc. 5 ft. over NW. slope.

20.00 Point for the E 1/16 sec. cor of secs. 6 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 31}{S\ 6}$
1974

from which

A fir, 6 ins. diam., bears N. 56 1/2° E., 12 lks. dist., mkd. E 1/16 S31 BT.

A fir, 6 ins. diam., bears S. 5° E., 13 lks. dist., mkd. E 1/16 S6 BT.

Descend 40 ft. over NW. slope.

23.55 Ravine, drains NE.; asc. 265 ft. over SE. slope.

33.00 Dirt road, 10 lks. wide, bears N. 10° E. and S. 10° W.

33.95 Ridge, bears N. & S; desc. 75 ft. over SW. slope.

34.90 Gravelled road, 15 lks. wide, bears N. 10° W. and S. 10° E.

40.00 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4 $\frac{S\ 31}{S\ 6}$
T 27 S
1974

from which

A white fir, 11 ins. diam., bears N. 37° W., 243 lks. dist., mkd. 1/4 S31 BT.