

County Surveyor's Record, Douglas County, Oregon

15161

Dependent Resurvey, Portion of South Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

Note: This W 1/16 Cor. is for Sec. 31 only. The marks referring to section 6 have been removed from the brass cap. See authorization memo dated April 24, 1990. File 9632 (OR 942)

CHAINS

A sawed fir stump, 28 ins. diam., bears S. 64° E.,
124 lks. dist., mkd. 1/4 S6 BT.

From this point, an unrecorded iron pipe, 1/2 in. diam., firmly set, projecting 8 ins. above ground, bears N. 50° 20' W., 0.05 chs. dist., from which locally established bearing trees:

A sawed fir stump, 58 ins. diam., bears N. 60° E.,
55 lks. dist, with glavanized nail with "W"
embossed on head, driven into base.

A sawed fir stump, 49 ins. diam., bears S. 77° E.,
55 1/2 lks.dist., with galvanized nail with "W"
embossed on head, driven into base.

Descend 110 ft. over NW. slope.

50.15 Ravine, drains N. 15° W.; asc. 15 ft. over NE. slope.

52.00 Spur, slopes N. 30° W.; desc. 110 ft. over SW. slope.

60.00 Point for the W 1/16 sec. cor. of secs. 6 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} W\ 1/16\ \frac{S\ 31}{S\ 6} \\ 1974 \end{array}$$

from which

A fir, 6 ins. diam., bears N. 26° E., 107 lks.
dist., mkd. W 1/16 S31 BT.

A fir, 8 ins. diam., bears S. 5° W., 67 1/2 lks.
dist., mkd. W 1/16 S6 BT.

Descend 20 ft. over SW. slope.

63.85 Dirt road, 15 lks. wide, bears N. 5° W. and S. 5° E.

65.70 Bottom of descent, slopes N.; asc. 140 ft. over NE. slope.

73.40 Ridge, bears N. and S.; desc. 40 ft. over NW. slope.

77.30 End of dirt road, 15 lks. wide, bears N. and S.

78.99 The cor. of Tps. 26 and 27 S., RS. 7 and 8 W., perpetuated and recorded by Bruce A. Shaner, Registered Logging Engineer No. 4906, in 1973, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

$$\begin{array}{r} T\ 26\ S \\ R.\ 8\ W\ R\ 7\ W \\ \hline S\ 36\ | S\ 31 \\ \hline S\ 1\ | S\ 6 \\ T\ 27\ S \\ 1973 \end{array}$$

from which the remains of the original bearing trees

A sawed cedar stump, 36 ins. diam., bears N. 20° E.,
118 lks. dist., with scribe marks T26S R7W S31 BT.