

# County Surveyor's Record, Douglas County, Oregon

**15163**

Dependent Resurvey, Portion of North Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 7 ins. diam., bears S. 49° W., 26 lks.  
dist., with healed blaze.

A madrone, 10 ins. diam., bears N. 55° W., 9 lks.  
dist., with scribe marks S31 T25S R7W visible  
on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 25 S R 7 W  
S 31 | S 32  
S 6 | S 5  
T 26 S  
1971

from which new bearing trees

A fir, 5 ins. diam., bears N. 78° E., 43 lks.  
dist., mkd. X BT.

A fir, 37 ins. diam., bears N. 12° W., 72 lks.  
dist., mkd. T25S R7W S31 BT.

N. 89° 34' W., bet. secs. 6 and 31, marking and blazing  
the true line.

Descend 480 ft. over SW. slope, through heavy timber and  
dense undergrowth.

15.85 Creek, 5 lks. wide, course S. 30° W.; asc. 15 ft. over  
NE. slope.

18.40 Spur, slopes S.; desc. 110 ft. over SW. slope.

23.75 Creek, 3 lks. wide, course N. 20° W.; asc. 175 ft. over  
NE. slope.

36.10 Spur, slopes N.; desc. 20 ft. over SW. slope.

37.70 Ravine, drains N.; asc. 125 ft. over NE. slope.

40.61 Point for the 1/4 sec. cor. of secs. 6 and 31, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins.  
long, 2 1/2 ins. diam.,  
24 ins. in the ground, with  
brass cap mkd.

T 25 S R 7 W  
1/4 S 31  
S 6  
T 26 S  
1971

*FO. OK 6/94 BY  
DeGROOT M119-33*

from which

A fir, 10 ins. diam., bears N. 41° W., 35 lks.  
dist., mkd. 1/4 S31 BT.

A fir, 15 ins. diam., bears S. 30° W., 24 lks.  
dist., mkd. 1/4 S6 BT.

Ascend 10 ft. over NE. slope.

41.85 Spur, slopes N. 30° E.; desc. 205 ft. over NW. slope.